

Revision Number: 001.2 Issue date: 11/20/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Fester Acriton Fachadas Liso Blanco Product type: Paints and coatings

Restriction of Use: None identified

Company address: Henkel Capital S.A. de C.V.

Boulevard Magnocentro 8 - P2

Huixquilucan Edo. de Mexico, C.P. 52760

IDH number: 1627631

Region: Mexico Contact information:

Telephone: +52 (55) 33003000

SETIQ,, Telephone 01-800-00-214-00 (5559-1588)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H315 - CAUSES SKIN IRRITATION.

H319 - CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention: P264 - Wash affected area thoroughly after handling.

P280 - Wear protective gloves, eye protection, and face protection.

Response: P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical attention. P337+P313 - If eye irritation persists: Get medical attention.

P362 - Take off contaminated clothing.

Not prescribed Storage: Disposal: Not prescribed

Classification complies with NOM-018-STPS-2015 and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	UN no.:	Percentage*
Limestone	1317-65-3		30 - 40
Titanium dioxide	13463-67-7		10 - 30

IDH number: 1627631 Product name: Fester Acriton Fachadas Liso Blanco

Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)	64742-48-9	0.1 - 1
Propane-1,2-diol	57-55-6	0.1 - 1
Quartz (SiO2)	14808-60-7	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Immediately remove victim to fresh air. Get immediate medical attention.

Skin contact: Rinse with running water and soap. If necessary, see a dermatologist.

Immediately wash skin thoroughly with soap and water. Remove contaminated clothes. Rinse immediately with plenty of running water, seek medical advice if

necessary.

Eye contact: Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek

medical attention. Take care not to rinse contaminated water into the

unaffected eye.

Ingestion: Do not induce vomiting. If adverse health effects develop seek medical

attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Fire fighters should wear positive pressure self-contained breathing apparatus

(SCBA).

Unusual fire or explosion hazards: Formation of toxic gases is possible during heating or in fires.

Hazardous combustion products: In case of fire toxic gases can be released.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: No special environmental precautions required.

Clean-up methods: None identified.

7. HANDLING AND STORAGE

Handling: Avoid naked flames, sparking and sources of ignition. Keep in a cool, well

ventilated area.

Storage: Not available.

IDH number: 1627631

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.		None
Titanium dioxide	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 10 mg/m3 TWA 10 mg/m3 TWA 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.		None	None
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)	None 100 ppm (400 mg/m3) PEL		None	196 ppm TWA
Propane-1,2-diol	None	None	10 mg/m3 TWA Aerosol.	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust.	None	None

Engineering controls: Ensure good ventilation/suction at the workplace.

Respiratory protection:Suitable breathing mask.Eye/face protection:Wear protective glasses.

Skin protection:Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: liquid Color: white Odor: Acrylic Odor threshold: Not available. pH: Not available. Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Vapor density: Not available.

Flash point: Aqueous. Does not flash.

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Flammability:

Evaporation rate:

Not available.

Not applicable

Not available.

IDH number: 1627631 Product name: Fester Acriton Fachadas Liso Blanco

Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Viscosity:
Not available.
Not available.
Not available.
Not available.
Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Reactivity: Not available.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

None if used for intended purpose.

Incompatible materials: None known

Conditions to avoid: None if used for intended purpose.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Heating this product may release harmful vapors. Abrasion of cured material such as by

sanding or grinding could release respirable particles of silica quartz, a cancer hazard by

inhalation. Normal use of this product causes no such release.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Limestone	None	Nuisance dust	
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity	
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)	None	Irritant	
Propane-1,2-diol	Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg	Irritant	
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Titanium dioxide	No	Group 2B	No
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)	No	No	No
Propane-1,2-diol	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains, soil or bodies of water.

IDH number: 1627631 Product name: Fester Acriton Fachadas Liso Blanco

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

Road transport ADR:

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

No additional information

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format., This Safety Data Sheet contains changes from the previous version in Section(s): 1,2,3,4,5,6,8,9,10,11,14,16

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/20/2017

DISCLAIMER: This information is considered correct, but it's not exhaustive and will be used only as a guide, which is based on current knowledge of the chemical substance(s) and/or mixture and apply to the appropriate product for safety precautions.

The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Capital does not assume responsibility for any results obtained by persons over whose methods Henkel Capital has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Capital's products. In light of the foregoing, Henkel Capital specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Capital's products. Henkel Capital further disclaims any liability for consequential or incidental damages of any kind, including lost profits.