



Revision Number: 001.0

Issue date: 12/08/2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Fester Acriton PS Max 12A Blanco 19L **IDH number:** 2970387
Product type/use: Coating
Restriction of Use: None identified **Region:** Mexico
Company address: **Contact information:**
 Henkel Capital S.A. de C.V. Telephone: +52 (55) 33003000
 Boulevard Magnocentro 8 – P2 SETIQ,, Telephone 01-800-00-214-00 (5559-1588)
 Huixquilucan Edo. de Mexico, C.P. 52760

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H319 - CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention: P264 - Wash affected area thoroughly after handling.
 P280 - Wear eye and face protection.
Response: P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 - If eye irritation persists: Get medical attention.
Storage: Not prescribed
Disposal: Not prescribed

Classification complies with NOM-018-STPS-2015 and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	UN no.:	Percentage*
Limestone	1317-65-3		30 - 60
Titanium dioxide	13463-67-7		5 - 10
Aluminium hydroxide	21645-51-2		0.1 - 1
Silicon dioxide	7631-86-9		0.1 - 1
potassium methylsilanetriolate	31795-24-1		0.1 - 1

IDH number: 2970387

Product name: Fester Acriton PS Max 12A Blanco 19L

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	72623-87-1		0.1 - 1
Cellulose	9004-34-6		0.1 - 1
Benzophenone	119-61-9		0.1 - 1
Quartz (SiO ₂), <1% respirable	14808-60-7		0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
Skin contact:	Immediately wash skin thoroughly with soap and water.
Eye contact:	Wash with plenty of water immediately and continue for several minutes, holding eyelid open. Consult a doctor. Check for and remove any contact lenses.
Ingestion:	Do not induce vomiting. Seek medical advice immediately and show this container or label.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray mist or foam. carbon dioxide extinguishing powder
Special firefighting procedures:	Wear self-contained breathing apparatus. Wear full protective clothing.
Unusual fire or explosion hazards:	In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO ₂) can be released.
Hazardous combustion products:	Carbon monoxide. Carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Contain spill. Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove mechanically. Wipe up using absorbent material.

7. HANDLING AND STORAGE

Handling:	Ensure that workrooms are adequately ventilated.
Storage:	Ensure adequate ventilation. Store in sealed original container. Store in a dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Aluminium hydroxide	1 mg/m3 TWA Respirable fraction. 10 mg/m3 TWA (as Al) Total dust. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	15 mg/m3 TWA (as Al) Total dust. 5 mg/m3 TWA (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust.	None	None
Silicon dioxide	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. 6 mg/m3 TWA	15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
potassium methylsilanetriolate	None	None	None	None
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	5 mg/m3 TWA Inhalable fraction.	None	None	None

Cellulose	10 mg/m3 TWA	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Benzophenone	None	None	0.5 mg/m3 TWA	None
Quartz (SiO ₂), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls:

Use only in well ventilated areas.

Respiratory protection:

Use an organic vapor respirator for concentrations exceeding the Occupational Exposure Limit.

Eye/face protection:

Safety glasses.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Color:	white
Odor:	Of acrylate
Odor threshold:	Not available.
pH:	9 - 10
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	> 100 °C (> 212°F) Estimated
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	Not available.
Viscosity:	45,000 - 50,000 cp
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Reactivity:	Not available.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	In case of fire toxic gases can be released.
Incompatible materials:	None if used for intended purpose.
Conditions to avoid:	Excessive heat.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	May irritate the nose and respiratory system. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	Repeated exposure may cause skin dryness or cracking.
Eye contact:	Causes eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity
Aluminium hydroxide	Oral LD50 (Rat) = > 5,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l	Irritant, Lung, Respiratory
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 2.08 mg/l Inhalation LC50 (Rat, 4 h) = > 0.69 mg/l	Nuisance dust
potassium methylsilanetriolate	None	No Data
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = > 5.53 mg/l	Irritant
Cellulose	None	Lung
Benzophenone	Oral LD50 (Mouse) = 2,895 mg/kg	Blood, Kidney, Irritant, Some evidence of carcinogenicity
Quartz (SiO ₂), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Titanium dioxide	No	Group 2B	No
Aluminium hydroxide	No	No	No
Silicon dioxide	No	No	No
potassium methylsilanetriolate	No	No	No
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	No	No	No
Cellulose	No	No	No
Benzophenone	No	Group 2B	No
Quartz (SiO ₂), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains, soil or bodies of water.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

Road transport ADR:

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

No additional information

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Corrected information in Section(s): 2, 3, 8, 11

Prepared by:	Product Safety and Regulatory Affairs
Issue date:	12/08/2023

DISCLAIMER: This information is considered correct, but it's not exhaustive and will be used only as a guide, which is based on current knowledge of the chemical substance(s) and/or mixture and apply to the appropriate product for safety precautions.

The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Capital does not assume responsibility for any results obtained by persons over whose methods Henkel Capital has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Capital's products. In light of the foregoing, Henkel Capital specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Capital's products. Henkel Capital further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Mexican Official Standard (NOM-018-STPS-2015) of the harmonized system for the identification and communication of hazards and risks from hazardous chemicals in the workplace and provides information in accordance with Mexican law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.