



Revision Number: 001.0

Issue date: 05/03/2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Fester Acriton Green-Shield 10 Años
Blanco
Product type/use: Acrylics
Restriction of Use: None identified
Company address: Henkel Capital S.A. de C.V.
 Boulevard Magnocentro 8 – P2
 Huixquilucan Edo. de Mexico, C.P. 52760

IDH number: 2931270
Region: Mexico
Contact information:
 Telephone: +52 (55) 33003000
 SETIQ., Telephone 01-800-00-214-00 (5559-1588)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H319 - CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention: P264 - Wash affected area thoroughly after handling.
 P280 - Wear eye and face protection.
Response: P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 - If eye irritation persists: Get medical attention.
Storage: Not prescribed
Disposal: Not prescribed

Classification complies with NOM-018-STPS-2015 and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	UN no.:	Percentage*
Limestone	1317-65-3		10 - 30
Titanium dioxide	13463-67-7		5 - 10
Aluminium hydroxide	21645-51-2		0.1 - 1
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	72623-87-1		0.1 - 1

IDH number: 2931270

Product name: Fester Acriton Green-Shield 10 Años Blanco

Zinc oxide	1314-13-2		0.1 - 1
Silicon dioxide	7631-86-9		0.1 - 1
Quartz (SiO ₂), <1% respirable	14808-60-7		0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Immediately remove victim to fresh air. Get medical attention.
Skin contact:	Wash with soap and water. Get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Get immediate medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	carbon dioxide, foam, powder, water spray jet, fine water spray
Special firefighting procedures:	Wear respiratory protection equipment according to ambient air conditions.
Unusual fire or explosion hazards:	Formation of toxic gases is possible during heating or in fires.
Hazardous combustion products:	Irritating and toxic gases or fumes may be released during a fire.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Remove with liquid-absorbing material (sand, peat, sawdust).

7. HANDLING AND STORAGE

Handling:	Ensure good ventilation/suction at the workplace.
Storage:	Ensure adequate ventilation. Store in sealed original container. Store in a dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Aluminium hydroxide	1 mg/m3 TWA Respirable fraction. 10 mg/m3 TWA (as Al) Total dust. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	15 mg/m3 TWA (as Al) Total dust. 5 mg/m3 TWA (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust.	None	None
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	5 mg/m3 TWA Inhalable fraction.	None	None	None
Zinc oxide	2 mg/m3 TWA Respirable fraction. 10 mg/m3 STEL Respirable fraction.	5 mg/m3 PEL Fume. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust.	None	None

Silicon dioxide	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. 6 mg/m3 TWA	15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Quartz (SiO ₂), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: Ensure good ventilation/suction at the workplace.

Respiratory protection: Ensure good ventilation/suction at the workplace.

Eyeface protection: Wear protective glasses.

Skin protection: Wear protective equipment. Use of Butyl or Nitrile Rubber gloves is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	white
Odor:	Of acrylate
Odor threshold:	Not available.
pH:	>= 9
Vapor pressure:	Not available.
Boiling point/range:	> 100 °C (> 212°F) Boiling point
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	Not available.
Viscosity:	50,000 - 60,000 cp
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions.
Reactivity:	Not available.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	In case of fire toxic gases can be released. No decomposition if used according to specifications.
Incompatible materials:	Strong oxidizing agents.
Conditions to avoid:	Stable under normal conditions of storage and use. Excessive heat.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. May cause slight irritation.
Skin contact:	Repeated exposure may cause skin dryness or cracking.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity
Aluminium hydroxide	Oral LD50 (Rat) = > 5,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l	Irritant, Lung, Respiratory
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = > 5.53 mg/l	Irritant
Zinc oxide	Oral LD50 (Mouse) = 7,950 mg/kg Oral LD50 (Rat) = > 5 g/kg Inhalation LC50 (Rat, 4 h) = > 5,700 mg/m3	Blood, Gastrointestinal, Immune system, Irritant, Kidney, Metabolic, Nervous System, Pancreas, Respiratory, Skin
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 2.08 mg/l Inhalation LC50 (Rat, 4 h) = > 0.69 mg/l	Nuisance dust
Quartz (SiO ₂), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Titanium dioxide	No	Group 2B	No
Aluminium hydroxide	No	No	No
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, <3% DMSO	No	No	No
Zinc oxide	No	No	No
Silicon dioxide	No	No	No
Quartz (SiO ₂), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains / surface water / ground water.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

Road transport ADR:

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

No additional information

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by:	Product Safety and Regulatory Affairs
Issue date:	05/03/2023

DISCLAIMER: This information is considered correct, but it's not exhaustive and will be used only as a guide, which is based on current knowledge of the chemical substance(s) and/or mixture and apply to the appropriate product for safety precautions.

The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Capital does not assume responsibility for any results obtained by persons over whose methods Henkel Capital has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Capital's products. In light of the foregoing, Henkel Capital specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Capital's products. Henkel Capital further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Mexican Official Standard (NOM-018-STPS-2015) of the harmonized system for the identification and communication of hazards and risks from hazardous chemicals in the workplace and provides information in accordance with Mexican law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.